

Date of Deposit: March 4, 2002

Our Case No.10541-264
Visteon Docket No.:V200-0152

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR(S): Kevin Allen Kieltyka
Srinivas Kotha

TITLE: COLOR TRIM PANEL

ATTORNEY(S): Steven L. Oberholtzer
Sujatha Subramaniam
BRINKS HOFER GILSON & LIONE
P.O. BOX 10395
CHICAGO, ILLINOIS 60610
(734) 302-6000

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

COLOR TRIM PANEL

TECHNICAL FIELD

[0001] This patent discloses and claims a useful, novel, and unobvious invention for a trim panel for use in motor vehicles. More specifically a trim panel formed from natural fiber mat and a method of making such trim panel is disclosed in the present application.

BACKGROUND

[0002] It is known to provide a trim panel assembly for an automotive vehicle to present an aesthetically pleasing appearance in an occupant compartment of the automotive vehicle. Trim panels have typically been used in headliners, instrument panels and doors. The current automotive interior styling trend is toward a softer, wrap-around styling vision which places special emphasis on the tactile feel of the interior, as well as the visual impression. The hard plastic substrates and surfaces of car interiors in past years are being replaced by the trend toward padded or cushioned surfaces, covered by either vinyl or textile materials. The automotive interior surfaces typically comprise a structural substrate of aluminum, plastic or which is relatively rigid. A layer of padding and a trim panel may cover the interior surface of the substrate. The surface of the trim panel which is exposed to the passenger are typically leather, vinyl or textile materials, including cloth or carpet. In addition a layer of foam is inserted between the substrate and the surface that is exposed to give the trim panel a tactile feel.

[0003] Current interior trim suppliers are using a variety of methods to apply the layer of exposed surface and padding to the substrates of various interior trim systems. The most common and least technologically advanced method is hand applying the coverings to the substrate. The layers are hand laid over a finished substrate and then pushed, pulled, tucked and pinched into the contour of the substrate. The layers are secured with adhesives and/or mechanical fasteners such as staples or the like. Obviously hand applied trim panels have high labor costs. Yet another method is vacuum forming and low-pressure molding (LPM). In LPM the trim panel is attached concurrently with the molding of the rigid substrate.

[0004] However, it is desirable to provide a trim panel assembly with reduced mass, tooling and equipment per vehicle. Therefore, there is a need in the art to provide an improved method of making a trim panel assembly for an automotive vehicle that has an integral cover skin and desired coloring for the trim panel.

SUMMARY

[0005] In one aspect of the present invention, a door panel installed in an interior of a motor vehicle comprises a first layer formed of a first material, a second layer formed of a second material, a third layer formed of a third material and a fourth layer formed of the same material as the second layer. The second and the fourth layer are adaptable to be molded such that they form the substrate of the door panel.

[0006] In yet another aspect of the present invention, a method of forming a door panel for an interior of a motor vehicle is disclosed. The method comprises forming the second layer and the fourth layer. Sandwiching the third layer between the second layer and the fourth layer. The first layer is then tacked on top of the second layer. The pre-formed layers are then inserted inside a molding tool and heated such that the first layer is integrally attached to the second layer.

BRIEF DESCRIPTION OF THE FIGURES

[0007] FIGURE 1 is a perspective view of a door panel insert, according to the preferred embodiment of the present invention; and

[0008] FIGURE 2 is a cross-sectional view of a portion of the door panel insert, showing the layers of the trim panel thereof in accordance with the preferred embodiment of the present invention; and

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0009] The following description of the preferred embodiments is merely exemplary in nature, and is in no way intended to limit the invention or its application or uses.

[0010] Referring in particular to Figures 1 and 2, a door panel insert installed in the interior of a motor vehicle in accordance with the teachings of the present invention is generally designated by reference numeral 10. Although not shown in

the drawings the door panel inset 10 is a part of a door of the motor vehicle. The door panel inset 10 defines an exterior surface 14 and is attached to a door panel substrate 18. Alternatively, the door panel inset 10 may be directly attached to a substrate such as an interior metallic sheet made of aluminum or a hard plastic substrate. The exterior surface 14 is exposed to the interior of the motor vehicle and is also known as a Class A surface.

[0011] It should be understood that the door panel inset 10 is only illustrated as an example. The insert formed by the method of this invention may be mounted to other panels of the motor vehicle such as instrument panels, headliners, arm rests, center consoles, seating, head rests, A, B or C pillars.

[0012] The door panel inset 10 in accordance with the teachings of the present invention is preferably attached to a door panel substrate 18. The door panel substrate 18 is relatively rigid than the door panel inset 10. This method of forming the door panel inset 10 can also be used to form the door panel substrate 18. The door panel inset 10 is attached to the door panel substrate 18 with the help of heat stacking process. Alternatively, the door panel inset 10 can be attached to the door panel substrate 18 with the help adhesives. Preferably, the adhesive used is a thermosetting adhesive such as cross linking urethane such that on heating it bonds the door panel inset 10 to the substrate 18.

[0013] The door panel inset 10 comprises a first layer or an outer decorative layer 20, a second layer 22, a third layer 24 and a fourth layer 26. The first layer 20 of the door panel inset 10 forms the exterior surface 14 or the class A surface. As will be explained later, the class A surface or the exterior surface 14 of the door panel inset is simultaneously formed with the formation of the substrate portion 22 and 26 of the door panel inset 10. As discussed above, first layer 20 is exposed to a passenger of the motor vehicle. The fourth layer 26 is attached to the door panel substrate 18. Preferably, the second layer 22 and the third layer 24 are sandwiched between the first layer 20 and the fourth layer 26. Alternatively, it is possible that the trim panel assembly 10 is formed with fewer than four layers. For example, the trim panel assembly may be formed only of the first layer 20, the second layer 22.

[0014] The first layer 20, as explained above is generally the layer that is exposed to the passenger of the motor vehicle. The first layer 20 is formed of a first

material. Preferably, the first material used to form the first layer 20 is extruded polypropylene. The process of obtaining an extruded polypropylene is well known in the art and is not explained in details. Alternatively, the first layer 20 could also be formed of a spun bond polypropylene. As will be explained later in either case, the first layer 20 is bonded to the upper surface 28 of the second layer 22. The thickness of the first layer 20 is determined by the density of the second layer 22. In order to manufacture a trim panel assembly 10 with the desired color, color may be added to polypropylene material. Alternatively, it is also possible to add more than one color to the first layer 20 such that the trim panel assembly 10 has more than one color. Additionally, it is also possible to add or control the grain size of the first layer 20.

[0015] The second layer 22 of the trim panel assembly 10 acts as a padding between the door panel substrate 18 and the first layer 20. Additionally, the second layer 22 also serves to impart structural integrity to the trim panel assembly 10. Preferably, the second layer 22 is formed of natural fiber composites. The natural fibers are derived from plants such as kenaf, hemp, flax, jute and sisal. These natural fibers are mixed with polypropylene and/or PET to form the natural fibers composites used in the present invention.

[0016] The third layer 24, in accordance with the teaching of the present invention is made of a recyclate material. In this invention by recyclate material it is meant any material that can typically be recycled into the environment when the trim panel assembly 10 is removed from the motor vehicle. The process of adding the recyclate material to the trim panel assembly 10 is explained in detail later. The third layer 24, is sandwiched between the second layer 22 and the fourth layer 26. Preferable the materials that are used to form the third layer 24 are selected from a group comprising of vinyl offal, or natural fiber offal.

[0017] The upper surface 30 of the fourth layer 26, is preferably attached to the third layer 24 and the lower surface 32 is preferably attached to the substrate 18. Suitable materials that are used to form the fourth layer 26 are preferably the same that are used to form second layer 22. Alternatively, different material may be used to form the second layer 24 and the fourth layer 26. It is also possible that the density of the second layer 22 is different from the density of the forth layer 26.

However, it is preferable that the second layer 22 and the fourth layer 26 have the same thermoformable temperature. In the preferred embodiments the materials used to form the fourth layer 26 of the trim panel assembly is natural fiber mat or alternatively may be a mixture of natural fiber and polypropylene fiber.

[0018] As shown in Fig. 2, the cross section of the door panel insert 10 comprises a first layer 20 formed of extruded polypropylene or spun bond polypropylene, and a second layer 22 formed of a natural mat that is adaptable to be molded into a substrate. Additionally, the door panel insert 10 comprises a third layer 24 formed of a recyclate material and a fourth layer 26 formed of the same material as the second layer. Both the second layer 24 and the fourth layer 26 are adaptable of being molded such that a need for a separate substrate is substantially eliminated.

[0019] The method of forming the door panel insert 10 comprises forming a pre-form wherein the first layer 20, second layer 22, third layer 24 and the fourth layer 26 are individually formed. Additionally, the second layer 22 and the fourth layer 26 are molded into a hard substrate during the compression molding process such that the door panel insert 10 can be attached to the door panel substrate 18. The first step of forming the pre-form of the door panel insert 10 comprises forming the second layer 22 and the fourth layer 26. The process of forming the second layer 22 and the fourth layer 26 from natural fiber mat composites is well known in the art and not explained in details. Briefly stated, the fibers from natural sources such as hemp is mixed with polypropylene fibers with the help of a binder material. Typically, the fibers are chopped to a desired size and mixed with the polypropylene fibers. The binding material is then added to the mixture of natural fiber and the polypropylene fibers and heated such that mat having the desired thickness is formed. The recyclate material forming the third layer 24 is obtained in a granular form. The granular form of the third material is heated and dropped on the top surface 30 of the fourth layer 26. The second layer 22 is then tacked on top of the third layer 24, such that the third layer 24 is sandwiched between the second layer 22 and the fourth layer 26. Finally, the first layer 20 is added on the top surface of the second layer 22.

[0020] After the pre-form comprising the individual layers are formed, the door panel insert 10 is inserted inside a molding tool. The molding tool is well known in the art and is not described in detail. The door panel insert 10 is then subjected to compression molding and heating such that a chemical bond is formed between the polypropylene fibers in the natural mat of the second layer 22 and the polypropylene fibers in the first layer 20. After undergoing the heating and compression the door panel insert 10 is taken out of the molding tool and attached to the door panel substrate 18 by the heat staking. Alternatively, adhesives may be used to attach the door panel insert 10 to the door panel substrate 18.

[0021] In this invention, the introduction of the third layer 24 formed of a recycle material allows for the door panel insert 10 to be recycled once the door panel insert 10 is removed from the motor vehicle. Additionally, it also allows for a door panel insert 10 or a door panel 18 having greater strength and the elimination to add a separate coverskin material to form the class A surface. As explained above, this process may be used to form the door panel 18.

[0022] As any person skilled in the art will recognize from the previous description and from the figures and claims, modifications and changes can be made to the preferred embodiments of the invention without departing from the scope of the invention.